



• B9000 • P9700 •

• **B9000** •

1002 250 cm	1003 - RAL 1014 250 cm	1018 - RAL 1018 250 cm	1021 - RAL 1021 218, 250 cm	1024 - RAL 1003 218, 250 cm
1059 - RAL 1032 250 cm	1622 250 cm	3002 218, 250 cm	3015 - RAL 3002 218, 250 cm	3021 - RAL 2008 218, 250 cm
3056 250 cm	5003 - RAL 5012 250 cm	5004 - RAL 5013 250 cm	5020 218, 250 cm	5031 - RAL 5010 218, 250 cm
5063 - RAL 5002 218, 250, 275 cm	5177 - PAN 273C 250 cm	6001 218, 250, 275 cm	6002 - RAL6001 250 cm	6027 - RAL 6018 250 cm
6028 - RAL6005 250 cm	7001 218, 250 cm	7002 - RAL 7035 250 cm	7003 218, 250, 275cm	7024 218, 250 cm
SILVER	7999 218, 250 cm	8020 - RAL 8017 250 cm	9002 150, 218, 238, 250, 275, 300 cm	9013 - RAL 9010 250 cm
7500 - RAL 9006 218, 250, 275, 300 cm				

• **P9700** •

9917 300 cm



# SIOEN

• B9000 • P9700 •

## COVERS



Fabric		100% PES 1100 dtex	
Weight	B9000 P9700	680 g/m <sup>2</sup> 700 g/m <sup>2</sup>	DIN EN ISO 2286-2
Lacquering		1/1	
Embossing		Glossy	
Breaking strength	Warp Weft	3000 N/5cm 2800 N/5cm	EN ISO 1421-1
Tear strength	Warp Weft	300 N 300 N	DIN 53 363
Adhesion		90 N/5cm	EN ISO 2411
Temperature resistance		-30/+70°C	DIN EN 1876-2
Light fastness	(except white and (half-) transparent)	7-8	ISO 105 B02
Fire behavior		<100 mm/min	ISO 3795
Application		Truck covers	



# SIOEN